TM 500W
6S4.501.352

TM 650W
6S4.651.352

TM 500W^{DV}
6S4.501.362

TM 650W^{DV}
6S4.651.362



		A	X %				Kg			
	V	A	35%	60%	100%	Dinse mm²	Kg	(LxWxH) mm	N° Steps	Ø mm
TM 500W	3x400	35 - 500	500 A	430 A	320 A	70	215	520x1.070x850	30	0.6 - 1.6
TM 500W^{DV}	3x230 - 3x400								21	
TM 650W	3x400	35 - 600	600 A	500 A (50%)	380 A		230		21	0.6 - 2.0
TM 650W^{DV}	3x230 - 3x400								21	



TM 500W	6S4.501.352
TM 500W^{DV}	6S4.501.362

CONFIGURAZIONE BASE DELLA MACCHINA
• Macchina fornita con motorino trainafilo 4 rulli • Rullini 0.8/1.0 - 1.2 /1.6 • Imballo in cartone.



TM 650W	6S4.651.352
TM 650W^{DV}	6S4.651.362

FACTORY CONFIGURATION
• 4 rolls wire-feeder motor • Rolls 0.8/1.0 - 1.2/1.6 • Carton box.

ACCESSORI OPZIONALI - OPTIONAL ACCESSORIES

	CODE		DESCRIZIONE	DESCRIPTION
	049.602.004		Cavo con morsetto di massa a pinza 50 mm² - dinse 50 mm² - 4 m	Cable with ground clamp 50 mm² - dinse 50 mm² - 4 m
	049.602.005		Cavo con morsetto di massa a pinza 70 mm² - dinse 50 mm² - 4 m	Cable with ground clamp 70 mm² - dinse 50 mm² - 4 m
	049.600.075	○	Cavo con morsetto di massa 70 mm² - dinse 70 mm² - 3 m	Cable with ground clamp 70 mm² - dinse 70 mm² - 3 m
	049.600.076	TM650	Cavo con morsetto di massa 95 mm² - dinse 70 mm² - 3 m	Cable with ground clamp 95 mm² - dinse 70 mm² - 3 m
	421.300.007		Kit staffe ruote Ø 100mm per wire feeder	Kit brackets wheel Ø 100mm for wire feeder
	580.000.402	○	Riduttore a 2 manometri + riduzione CO_2 /Argon	Reducer two gauges + reduction CO_2 /Argon

AIR KIT

	043.600.143	○	Torcia F36 - 4 m - 320A@60%	Torch F36 - 4 m - 320A@60%
	422.990.031	○	Fascio cavi 1,5 m D.50 mm² Aria	Extension lead cable 1,5 m D.50 mm² Air
	422.990.032		Fascio cavi 5,0 m D.50 mm² Aria	Extension lead cable 5,0 m D.50 mm² Air
	422.990.043		Fascio cavi 10 m D.70 mm² Aria	Extension lead cable 10 m D.70 mm² Air
	422.990.047		Fascio cavi 30 m D.70 mm² Aria	Extension lead cable 30 m D.70 mm² Air
	422.990.049		Fascio cavi 50 m D.70 mm² Aria	Extension lead cable 50 m D.70 mm² Air
	422.990.051		Fascio cavi 1,5 m D.95 mm² Aria	Extension lead cable 1,5 m D.95 mm² Air
	422.990.052		Fascio cavi 5,0 m D.95 mm² Aria	Extension lead cable 5,0 m D.95 mm² Air
	422.990.053		Fascio cavi 10 m D.95 mm² Aria	Extension lead cable 10 m D.95 mm² Air
	422.990.057		Fascio cavi 30 m D.95 mm² Aria	Extension lead cable 30 m D.95 mm² Air
	422.990.059		Fascio cavi 50 m D.95 mm² Aria	Extension lead cable 50 m D.95 mm² Air

AIR H_2O

	580.523.053	○	Unità di raffreddamento	Water cooling unit
	920.500.042	○	Fluido refrigerante 5l per Unità	Cooling fluid 5l
	920.500.043		Fluido refrigerante 10l per Unità	Cooling fluid 10l
	043.600.144		Torcia F51 H_2O - 3 m - 430A@100%	Torch F51 H_2O - 3 m - 430A@100%
	043.600.145	○	Torcia F51 H_2O - 4 m - 430A@100%	Torch F51 H_2O - 4 m - 430A@100%
	422.990.131	○	Fascio cavi 1,5 m D.50 mm² H_2O	Extension lead cable 1,5 m D.50 mm² H_2O
	422.990.142		Fascio cavi 5,0 m D.70 mm² H_2O	Extension lead cable 5,0 m D.70 mm² H_2O
	422.990.143		Fascio cavi 10 m D.70 mm² H_2O	Extension lead cable 10 m D.70 mm² H_2O
	422.990.144		Fascio cavi 15 m D.70 mm² H_2O	Extension lead cable 15 m D.70 mm² H_2O
	422.990.151		Fascio cavi 1,5 m D.95 mm² H_2O	Extension lead cable 1,5 m D.95 mm² H_2O
	422.990.152		Fascio cavi 5,0 m D.95 mm² H_2O	Extension lead cable 5,0 m D.95 mm² H_2O
	422.990.153		Fascio cavi 10 m D.95 mm² H_2O	Extension lead cable 10 m D.95 mm² H_2O
	422.990.154		Fascio cavi 15 m D.95 mm² H_2O	Extension lead cable 15 m D.95 mm² H_2O

RULLINI - ROLLS

	422.520.002	●	Rullino 0,8-1,0 D.37 -keyway - V cava (acciaio, acciaio inossidabile)	Roll 0,8-1,0 D.37 - keyway - V groove (steel, stainless steel)
	422.520.003		Rullino 1,0-1,2 D.37 -keyway - V cava (acciaio, acciaio inossidabile)	Roll 1,0-1,2 D.37 - keyway - V groove (steel, stainless steel)
	422.520.004	●	Rullino 1,2-1,6 D.37 -keyway - V cava (acciaio, acciaio inossidabile)	Roll 1,2-1,6 D.37 - keyway - V groove (steel, stainless steel)
	422.520.051		Rullino 0,8-1,0 D.37 -keyway - U cava (alluminio)	Roll 0,8-1,0 D.37 - keyway - U groove (aluminium)
	422.520.052		Rullino 1,0-1,2 D.37 -keyway - U cava (alluminio)	Roll 1,0-1,2 D.37 - keyway - U groove (aluminium)
	422.520.053		Rullino 1,2-1,6 D.37 -keyway - U cava (alluminio)	Roll 1,2-1,6 D.37 - keyway - U groove (aluminium)
	422.520.101		Rullino 1,2-1,6 D.37 -keyway - Cava zigrinata (filo animato)	Roll 1,2-1,6 D.37 - keyway - Knurled groove (flux cored)
	422.520.102		Rullino 1,6-2,4 D.37 -keyway - Cava zigrinata (filo animato)	Roll 1,6-2,4 D.37 - keyway - Knurled groove (flux cored)
	422.520.103		Rullino 1,0-1,2 D.37 -keyway - Cava zigrinata (filo animato)	Roll 1,0-1,2 D.37 - keyway - Knurled groove (flux cored)